










Dust seals for reciprocal movement

Type	NOK type	Cross section	Standard material	Main application fluid	Feature			
Dust seals	DKI	 (Combination)	1) Lip material Noxlan (U801)  Metal case material, Cold rolled steel plate sheet (SPCC) 2)	<ul style="list-style-type: none"> <li>• Outside dust</li> </ul>	<ul style="list-style-type: none"> <li>• This is a seal to prevent entry of dust and protect equipment and maintain sealing performance of packings.</li> </ul>	<ul style="list-style-type: none"> <li>• This is a standard type of dust seal of noxlan with high dust proof performance.</li> </ul>		
	DWI		1) Lip material Noxlan (U801)  Metal case material, Cold rolled steel plate sheet (SPCC) 2)				<ul style="list-style-type: none"> <li>• Employing noxlan as material, this seal serves under severe dust conditions such as construction equipment.</li> </ul>	
	DWIR		1) Lip material Noxlan (U801)  Metal case material, Cold rolled steel plate sheet (SPCC) 2)				<ul style="list-style-type: none"> <li>• Employing noxlan as material, this has the same performance as DWI, excellent in preventing of oil scraping off and in followability to the eccentricity.</li> </ul>	
	DKBI		1) Lip material Noxlan (U801)  Metal case material, Cold rolled steel plate sheet (SPCC) 2)				<ul style="list-style-type: none"> <li>• Employing noxlan as material, this is a double-lip dust seal to prevent oil scraping off.</li> </ul>	
	DKB		1) Lip material Nitrile rubber (A795) (A980) Fluoro rubber (F384)  Metal case material, Cold rolled steel plate sheet (SPCC) 2)				A795	<ul style="list-style-type: none"> <li>• Employing nitrile rubber as material, this is a double-lip dust seal to prevent oil scraping off.</li> </ul>
							A980	
							F384	
	DKH		1) Lip material Nitrile rubber (A104) (A795) (A980) Fluoro rubber (F384)  Metal case material, Cold rolled steel plate sheet (SPCC) 2)				A104 A795	<ul style="list-style-type: none"> <li>• Employing nitrile rubber as material, this is a single-lip dust seal.</li> <li>• Material A795: for diameter Ø 300 or less A104: for diameter over Ø 300</li> </ul>
							A980	
							F384	
DSI		Noxlan (U801)	<ul style="list-style-type: none"> <li>• This is a seal to prevent entry of dust and protect equipment and maintain sealing performance of packings.</li> <li>• This can be fitted into a integrated groove.</li> </ul>	<ul style="list-style-type: none"> <li>• Employing noxlan as material, this is a single-lip all rubber dust seal.</li> </ul>				
LBI		Noxlan (U593)		<ul style="list-style-type: none"> <li>• Employing noxlan as material, this is a double-lip all rubber dust seal to prevent oil scraping off..</li> </ul>				
LBH		1) Lip material Nitrile rubber (A505) (A903) Fluoro rubber (F357)		A505	<ul style="list-style-type: none"> <li>• This is double-lip all rubber dust seal to prevent oil scraping off.</li> <li>• Nitrile rubber and fluoro rubber are available as material for wide range of operating temperature.</li> </ul>			
			A903					
			A980					